

# XT-1815P

15-inch Mountable Touch POS



## Key Features

- 15-inch TFT LCD w/ True-Flat PCAP (G+G) and 5-wire Resistive Touch
- Intel Core™ i3-1215U - 10M Cache, up to 4.40 GHz
- Fanless cooling system for silent and efficient operation
- 8GB DDR4 RAM (2 x DDR4 SO-DIMM slots, 3200MTs, up to 64GB)
- 128GB M.2 SSD and PCIe\*4
- VESA mount installation with seamless integration



Fanless & Slim Design



Rich I/O Interfaces



Angle Adjustable

## Specifications

XT-1815P	
<b>Processor</b>	Intel® Core™ i3-1215U
<b>System Memory</b>	8GB DDR4 RAM (2 x DDR4 SO-DIMM slots, 3200MTs, up to 64GB)
<b>Storage</b>	128GB Easy access M.2 SSD (PCIe 4.0 x 4 NVMe / SATA)
<b>LCD Panel</b>	15-inch TFT LCD, 1024 x 768
<b>Touch Panel</b>	True-Flat Projected Capacitive Multi Touch True- Flat 5-wire Resistive Touch
<b>Speaker</b>	1 x 2W High Quality Speaker
I/O Interface	
<b>USB</b>	3 x USB 3.2 Type A 1 x USB 3.2 Type C (w/ DP) 3 x USB 2.0 Type A (On Side of Unit – 2 Left, 1 Right)
<b>LAN</b>	1 x RJ45 10/100/1000Mbps Giga Ethernet
<b>COM</b>	2 x COM (RJ45), w/ RI/5V/12V by BIOS 1 x COM (DB9), w/ RI/5V/12V by Jumper (Option)
<b>VGA</b>	1 x DB-15 VGA Port (Option)
<b>HDMI</b>	1 x HDMI Port
<b>Audio</b>	1 x Line-out/MIC-in
<b>Cash Drawer</b>	1 x RJ11 port supports 2 cash drawer, w/ 12V/24V by jumper
<b>DC Power Out</b>	1 x DC 12V Power Out (DC 2.1mm)
<b>DC Power In</b>	1 x Standard DIN 4pin type
Power Management	
<b>Power Adapter</b>	12V@7.5A, 90W Adapter
Mechanical & Environmental	
<b>Dust and Water</b>	IP65 on Front Bezel
<b>Tilt Adjustment</b>	0° ~ 90°
<b>Dimensions</b>	378.31 (W) x 282.47 (H) x 45.7 (D) mm
<b>Weight</b>	3.75 kg
<b>Certification</b>	CE/FCC/LVD
<b>Operating System</b>	Windows 10/11
<b>TPM</b>	TPM2.0
<b>Operating Conditions</b>	0°C to +40°C / 20 to 80% without condensation
<b>Storage Conditions</b>	-20°C to +60°C / 20 to 85% without condensation
Optional Accessories	
<b>2nd Display</b>	9.7" (1024 x 768) LCD Display (Optional PCAP Touchscreen)
<b>Customer Display</b>	VFD and LCD Customer Display
<b>MSR (Right Side)</b>	Bi-directional, Comply with ISO 7811 and Three Track support
<b>Wi-Fi (Left Side)</b>	Wi-Fi IEEE 802.11 a/b/g/n/ac
<b>NFC (Left Side)</b>	RFID 13.56 MHz, Comply Mifare, ISO14443AB-4 and Felica
<b>VESA Bracket</b>	VESA-Compatible, 75 x 75 (mm)